



## Leak Detection Module AT-LDM

DATA SHEET

### Description

The AquiTron™ AT- LDM offers a low cost option for liquid leak detection. It is designed for use with all TraceTek sensing cables, AquiTron™ probes and other sensing devices to detect leaks. The AT-LDM provides visual indication when a leak has occurred and has relay contacts to connect to other external alarm equipment. An option is available with an audible alarm.

Each module comes in two forms; either with DIN rail mounting frame or polycarbonate enclosure together with comprehensive installation instructions.

### Simple Operation

Two LED's to indicate the operating status of the unit:

- POWER – alarm unit power (green)
- LEAK – liquid detected (red)

### Application

Primarily designed for small area detection in locations such as Tea Points, Kitchens, Bunded area's and Drip Trays, or alternatively these units can be used with the AquiTron™ AT-RWS-1 Rain Sensor.

Because of their compact size these modules can normally be easily incorporated into OEM equipment or outstation enclosures thus saving the cost of a dedicated enclosure.

Modules can be sited close to the area to be monitored or mounted up to 200 metres away in control equipment.

AT-LDM-SM housed in a polycarbonate enclosure



AT-LDM & AT-LDM-S open chassis, DIN rail mounting



### Technical Information

Sensing cable compatibility	All TraceTek adapted sensing cable (TT1000, 3000, 5000, 5001 and 7000 )
Detection Probes	Water detection probes, optical oil sensors, float switches and immersion sensors
Maximum length of sensing cable	45 metres (150 ft) Combination of any 10 AquiTron™ probes
Enclosed version	Polycarbonate; smoked transparent lid, base & grey base; IP 66
Operating Conditions (PCB)	-10 to +50° C, 0% to 90% non-condensing
Power supply	Two versions: 24V ac/dc & 230Vac (ac 50/60Hz)
Power consumption	50 mA @ 24V ac/dc and 11mA @ 230Vac
Relay Output	Volt free relay contacts activated by leak SPDT (NC/COM & NO)
Relay Rating	5 A at 250 Vac/24 Vdc
Status LED	Power (Green), Leak (Red)
Audible Alarm	85dB 10cm (where fitted)
Dimensions	Open chassis: 77mm x 112mm x 45mm Enclosed: 130mm x 130mm x 75mm
Weight	Open chassis: 82g ~ 24V version & 248g ~ 230V version Enclosed: 660g

---

**Approvals**

Electromagnetic compatibility (EMC)



---

Ordering information	Catalogue number	4200	AT-LDM	Open Chassis: 24Vac
		4205	AT-LDM-S	Open Chassis: 24Vac with sounder
		4210	AT-LDM	Open Chassis: 230Vac
		4215	AT-LDM-S	Open Chassis: 230Vac with sounder
		4220	AT-LDM-SM	Enclosed: 230Vac with sounder & mute

---

**Operational Notes**

All Modules are Auto Reset and the relay contacts will remain activated as long as the sensor is wet.

On Modules with sounders fitted the sounder can be temporarily silenced by removing a link on the open chassis version or operating the switch on the enclosed versions.

---

**Resikom Limited**

**3 Kent Road, Dagenham, Essex, RM10 8HA,  
United Kingdom**

**Tel: +44 (0) 845 686 6066**

**Fax: +44 (0) 845 686 6067**

**Email: [info@resikom.com](mailto:info@resikom.com)**

**Web: [www.resikom.com](http://www.resikom.com)**