



3 Kent Road, Dagenham, Essex, RM10 8HA,  
United Kingdom

Tel: +44 (0) 845 686 6066

Fax: +44 (0) 845 686 6067

Email: [info@resikom.com](mailto:info@resikom.com)

Web: [www.resikom.com](http://www.resikom.com)

## Floodline Groundhog Mk II



The Floodline Groundhog Mk II is a self-contained, single-zone leak detection system which can be mounted vertically or horizontally. It can be connected to any control/building management system that has the facility to accept volt-free contacts.

Additional Floodline Point Sensors or Leak Detection Tape can be slaved off the Groundhog.

**Function:**  
Water/Liquid detection

**Zone Capacity:**  
1

**Power:**  
Multi-voltage operation 12 or 24V AC or DC at 0.8watts

**Construction:**  
Built into a stainless steel Guard Plate which provides protection and assists fixing

**Dimensions:**  
L130 x W90 x D37 mm

**Fixing:**  
Fixed or free-standing on floor or in drip tray  
Vertically at base of wall or plant

**Monitoring:**  
**LEAK** - continuous water/liquid built-in sensor and aux sensor input  
**SYSTEM FAULT** - aux sensor or Leader Cable damage, failure or disconnection

**Alarm Indicator:**  
Flashing LEDs for LEAK and SYSTEM FAULT  
All alarms displayed separately and continuously until corrected and reset if in manual mode

**Status Indicator:**  
Power LED

**Controls:**

Manual/Auto reset select  
Sensitivity setting

**Outputs:**

Leak/system fault - SPCO Relay  
1Amp@24Vdc



E&OE 06r01

